PRESSURE METER INCL. DATALOGGER

PCE-PDA 1L-ICA



- **Graphic display with lighting**
- **Min and Max value memory**
- **Data logger and leak test**
- **Quick coupling connection**
- **Temperature measurement, flow measurement**
- **High precision measuring mode**
- **Simple operation (voice-controlled)**
- **units switchable (Pa, kPa, hPa, ...)**
- **incl. ISO-Calibration Certificate**

The differential pressure gauges of the series are reliable differential pressure gauges for pressure measurement of gasses in the range of ± 2 Pa, ± 2kPa and 2 kPa depending on the model. The differential pressure gauge has many different pressure measuring functions. This gives the user more than 16 units. Furthermore, the differential pressure gauge measures in addition to the differential pressure, the temperature, flow velocity and volume flow. In addition, the maximum and minimum differential pressure can be displayed in the two-part graphic display. The resolution of the differential pressure can optionally be switched. The differential pressure gauge incorporates a high-precision mode that increases the resolution tenfold.

The PCE-PDA differential pressure gauge has a data logger function. This makes it possible to carry out a leak test on pressure lines in addition to the continuous storage of the measured values.

Specification

Differential pressure	
Measuring range	-2 ... +2 kPa
Resolution	0,1 Pa
Accuracy	±0.5% v.E.
Temperature	
Measuring range	0 ... 50 °C
Resolution	0,1 °C
Accuracy	±1°C

General technical data	
Measuring functions	MIN, MAX, HOLD, ALARM, Average value
Units	kPa, MPa, Pa, PSF, psi, Torr, inHg, mmHg, inH2O, cmH2O, mmH2O, kg/cm^2, atm, bar, mbar, hPa
Connections	5 mm nipple for quick connector
Display Typ	LCD graphic display with illumination
Display size	3 Inch
Display refresh rate	5 x per second
Measuring rate	10 Hz
Storage medium	Internal memory
Storage capacity	1024 Values
Storage interval from	1 s
Storage interval until	255 h
Interface	Micro-USB
Current consumption measuring device	50 mA DC
Measuring medium	non-explosive gases, Air
Operating time	100 h
Automatic power-off	255 min.
Housing	ABS
Overpressure	10 kPa
Menu language	English (US), German, English (GB), Czech
Protection class (device)	IP41
Power supply	5 V, 500 mA
Connector type	Device Europlug
Battery/battery	2 x 1,2 V AA - rechargeable battery , Nickel-metal hydride battery
Battery capacity	2000 mAh
Operating conditions	0 ... 50 °C , 0 ... 90 %RH
Storage conditions	10 ... 55 °C , 0 ... 80 %RH
Dimensions (L x W x H)	170 x 100 x 30 mm
Weight	230 g

PCE Americas Inc. dba PCE Instruments
1201 Jupiter Park Drive, Suite 8
Jupiter, FL 33458
USA

Phone: +1-561-320-9162
info@pce-americas.com