DIGITAL REFRACTOMETER

PCE-DRG 10



- **quick and accurate measurement in approx. 1 s**
- **large LC display (measured value and temperature)**
- **easy to use (1-key operation)**
- **small sample volume**
- **simple calibration with distilled water**
- **automatic temperature compensation**
- **stainless steel sample holder with glass prism**
- **automatic power-off after 1 min of inactivity**

Our digital refractometer determines the percentage of sodium hydroxide in aqueous media with a measurement range of 0 to 55 %. The measurement result and the temperature of the sample are shown in two lines on the LCD display of the digital refractometer. Our digital refractometer can measure various parameters and the refractive index quickly and accurately with just four to five drops of the sample. The digital refractometer has a wide range of applications: it can be used in water analysis, in the chemical industry or in the manufacture of products containing sodium hydroxide.

The funnel-shaped stainless steel ring protects the glass prism from damage, into which the liquid sample to be measured is placed. The internal light source enables measurement under poor lighting conditions. Our digital refractometer is supplied in a rugged plastic case with pipette and charging cable.

Specification

Refractive index	
Measuring range	1,325 ... 1,441 nD
Resolution	0,0001 nD
Accuracy	±0.0003 nD
Sodium hydroxide	
Measuring range	0 ... 55 %
Resolution	0,1 %
Accuracy	±0.2%
Temperature	
Measuring range	0 ... 40 °C
Resolution	0,1 °C
Accuracy	±0.5 °C

General technical data	
Temperature compensation	automatic 10 ... 40 °C
Display type	LCD
Measuring rate	1 Hz
Automatic power-off	1 min
Sample quantity	0,2 ... 0.3 ml
Menu language	English, English (GB)
Protection class (device)	IP65
Power supply	5V DC, 500mA
(Rechargeable) battery	1 x 3,7 V LP562438 , Lithium-ion polymer battery
Capacity	500 mAh
Performance	1,85 Wh
Operating conditions	0 ... 50 °C , 0 ... 95 % RH
Storage conditions	0 ... 50 °C , 0 ... 95 % RH
Dimensions (L x W x H)	145 x 46 x 27 mm
Weight	115 g

PCE Instruments UK Ltd.
Chester Rd, Old Trafford Suite 1N-B, Trafford House, M32 0RS Manchester
Great Britain

Phone: +44 (0) 161 464902 0
info@pce-instruments.co.uk