DUROMETER PCE-DDO 10 SHORE O-ICA

PCE-DDO 10-ICA



- **Handheld device**
- **Digital display**
- **Plastic case included**
- **For Shore O measurements**
- **Large display**
- **Single and Serial-Measurements**
- **Datatransfer to pc**
- **incl. ISO-Calibration Certificate**

The PCE-DDO 10 durometer is an ergonomic device to check Shore hardness in gum. It has been designed with a high quality. The PCE-DDO 10 durometer is mainly used for soft gums. If the material thickness is not enough, it should be tightened on the back with the same material in order to increase its thickness.

Specification

Hardness	
Measuring range	0 ... 100 Shore 0
Resolution	0,1 Shore 0
Accuracy	±1 Shore 0

General technical data	
Measuring functions	MAX, Average value
Measuring principle	Spring load
Storage medium	Internal memory
Storage capacity	500 Measurements
Interface	Mini-USB
Standard(s)	GB/T 531.1, ISO7619-1, ASTM D 2240
Operating time	20 h
Charging time	3 h
Impact device	D-type
Dimensions	Indentor / geometry: - Spring pin diameter: 2.38 mm ± 0.08 - Ball diameter: 1.19 mm ± 0.05
Menu language	English, English (GB)
Protection class (device)	IP20
Power supply	3.6V
Connector type	Device-europlug
(Rechargeable) battery	3 x 1,2 V AAA rechargeable battery , Nickel-metal hydride battery
Capacity	1200 mAh
Operating conditions	0 ... 50 °C , 20 ... 85 % RH
Storage conditions	-30 ... 80 °C , 5 ... 95 % RH
Dimensions (L x W x H)	153 x 50 x 29 mm
Weight	170 g