WATER LEVEL CONTROLLER

PCE-WLC 10



Specification

Sensor	
Designation	PCE-WLC-S
Measuring range with	0 ... 8 mH2O
Accuracy	±0.5 % FS
Battery type	Hydrostatic
Output	4 ... 20mA
Temperature range	-10 ... 70 °C
Housing	titanium alloy
cable length	10 m
Power supply	12 ... 30 V DC
Protection class	IP68
Dimension	L: 90 mm x Ø 28 mm / 3.5 in × Ø 1.1 in

General technical data	
Inputs	4 ... 20mA
Input (additional information)	For entrance areas and further details, see instructions
Outputs	Relay, 4 ... 20mA
Outputs	Relay changeover contact 24V / 5 A
Display Typ	LED
Alarm modes	4-way relay (AHH, AH, AL, ALL) with LED display Alarm limits adjustable on the controller
Protection class (device)	IP65
Power supply	24 V DC
Operating conditions	0 ... 50 °C , 0 ... 85 %RH
Storage conditions	-20 ... 70 °C , 10 ... 90 %RH
Dimensions (L x W x H)	95 x 80 x 160 mm
Weight	337 g

PCE Americas Inc. dba PCE Instruments
1201 Jupiter Park Drive, Suite 8
Jupiter, FL 33458
USA

Phone: +1-561-320-9162
info@pce-americas.com