PANEL INDICATOR

PCE-DPD-U



- **IP 65 on the front**
- **Different units possible**
- **Digital display for industrial processes**
- **Optional outputs**
- **4-digit digital display**
- **Many sensors can be connected**

The multi-signal digital panel indicator is configurable to work as voltmeter, ammeter, process signals (mA) with and without excitation voltage, temperature, resistors, potentiometers and frequencies. The digital panel indicator has a size of 96 x 48 mm and displays the values on a 4-digit LED display. The measurement range is 9999 to -1999 with selectable decimal point. The indicator has quick access to alarms setpoint, external contact for special functions, Eco mode of reduced consumption, 5 brightness levels.
The supply voltage of the multi-signal digital panel indicator from 18 to 265V AC / DC. Optionally the indicator can have relay output, analog output and Modbus RTU communications.

Specification

General technical data	
Display type	LED
Digit size [WxH]	H: 14 mm
Warm-up time	15 min
Housing	ABS (acrylonitrile-butadiene-styrene copolymers)
Mounting	Panel
Insulation	1500V RMS
Dimensions	Front size: 96 x 48 mm Panel cut-out: 92 mm x 45 mm (according to DIN)
Max. input voltage	≤30V DC
Display range	-199999 ... 999999
Additional description	Input impedance: dependent on the input signal and measuring range
Protection class (device)	IP65
Power supply	18 ... 265 V AC/DC
Operating conditions	0 ... 50 °C , 0 ... 80 % RH
Storage conditions	-20 ... 70 °C , 0 ... 80 % RH
Dimensions (L x W x H)	98 x 96 x 48 mm
Weight	138 g

PCE Instruments UK Ltd.
Chester Rd, Old Trafford Suite 1N-B, Trafford House, M32 0RS Manchester
Great Britain

Phone: +44 (0) 161 464902 0
info@pce-instruments.co.uk