INDUSTRIAL SCALE PCE-TB 1.5

PCE-TB 1,5



- **Item counting function**
- **8 different weighing units**
- **Weight compare in percentage %**
- **Filter (response time) adjustable**
- **Animal weighing function**
- **Max. weighing**

The industrial scale stands out due to its multifunctional range of application. But not only the large range of functions of the industrial scale is outstanding, the communication options of the industrial scale are interesting as well. The industrial scale features a bi-directional RS-232 interface and USB interface. Thus the industrial scale provides a very good foundation for every programmer (description of interface in instruction manual). The industrial scale sends the information via keypress automatically to a computer either every time the weighing value is stable, continuously (approx. 10 values per second) or on demand. Another option to integrate the industrial scale into a system would be the optionally purchasable interfaces, e.g. LAN-, analogue output 4 ... 20 mA or 0 ... 10 V as well as the weightlimit function with three potential-free contacts.

Interesting functions of the industrial scale are item-counting, percentage - calculation, formulation weighing, animal weighing, statistical weighing, summation function, threshold function, various weighing functions etc. The industrial scale can operate by battery as well as via adapter, and is also applicable for mobile weighing tasks. Via the optional ProCell software you can import the weighing data of the industrial scale into any system, where the data can be fed-in by keypress, such as Excel, Word, DHL, SAP etc. since the software simulates a manual data feed-in.

Specification

Weighing range	
Measuring range from	0 kg
Measurement range up to [Max]	1,5 kg
Resolution [d]	0,05 g
Accuracy	±0.2 g

General technical data	
Measuring functions	MIN, MAX
Measuring functions (additional information)	Piece counting function, percentage % comparison weighing, statistics function, totalisation function, animal weighing function
Units	kg, g, lb, oz, ct, ozt, gr, dwt, mg
Display type	LCD with backlight
Digit size [WxH]	Height 30 mm
Interface	USB, RS232C
Automatic power-off	5 min
Repeatability	0,1 g
Tare range	over the full weighing range
Weighing plate dimensions	B 300 x T 210 mm
Calibration	external
Settling time	< 3 s
Linearity	0.15 g
Menu language	English, English (GB)
Protection class (device)	IP54
Power supply	230V AC | 50 Hz, 6 VA 12V DC 1.2 A
Connector type	Device-europlug
(Rechargeable) battery	1 x 3 V CR 2032 (button cell 3V) , lithium-ion battery
Capacity	220 mAh
Operating conditions	-10 ... 40 °C , 15 ... 85 % RH
Storage conditions	-10 ... 40 °C , 15 ... 85 % RH
Dimensions (L x W x H)	350 x 328 x 115 mm
Weight	3500 g

PCE Instruments UK Ltd.
Chester Rd, Old Trafford Suite 1N-B, Trafford House, M32 0RS Manchester
Great Britain

Phone: +44 (0) 161 4649020
info@pce-instruments.co.uk