ISO FLOW CUP

PCE-128/6



- **Highly polished and finely machined for a**
- **high discharge accuracy**
- **Factory calibration certificate included**
- **With overflow channel**
- **Complies with international standards**
- **Stand available as optional accessory**

ISO flow cup meters are suitable for determining the flow time of Newtonian / near-Newtonian liquids and are often used in laboratories and industrial production. For handling, the nozzle must be closed and the material to be measured must be poured into the flow cup. By placing the glass plate on the cup, you create a vacuum, which enables the cup to be placed in the tripod for time measurement. When the glass plate is then pulled from the flow cup, the measurement can be started. As soon as the flow comes to a standstill, the time must be stopped. For a relative value, this method is perfectly adequate in many areas. To ensure the accuracy of the cup, it is important to clean it after each use. It is important to ensure that the surface inside the cup is not damaged. Any scratches or dried material residues will affect the further measurements.

Specification

Viscosity	
Measuring range	188 ... 684 mm^2/s

General technical data	
Display Typ	without display
Norm(en)	ISO 2431, DIN 53224, EN 535, ASTM D5125
Housing	Stainless steel
Outlet nozzle diameter	6 mm
Run-down time	30 ... 100 s
Dimensions	Outer diameter: 85 mm Inner diameter: 50 mm Cup height: 85 mm
Operating conditions	10 ... 40 °C , 20 ... 80 %RH
Storage conditions	10 ... 40 °C , 20 ... 80 %RH
Dimensions (L x W x H)	85 x 85 x 85 mm
Weight	353 g

PCE Americas Inc. dba PCE Instruments
1201 Jupiter Park Drive, Suite 8
Jupiter, FL 33458
USA

Phone: +1-561-320-9162
info@pce-americas.com