LEAK DETECTOR

PCE-LD 1



- **Detects R-134a, R-44A, Freon R-47C, R-41A and R-22 (per EN 14624)**
- **High / low sensitivity per SAE J1627 rating criteria**
- **Audible and visual alarms**
- **Easy to use**
- **Tricolor LED indicator shows concentration of gas**
- **Sensor life: Approx. 1 year - see accessories for replacement**

A portable handheld gas detector used to locate CFC/HFC refrigerant gas leaks. This highly sensitive gas leak detector can locate gas leaks from HVACR refrigeration systems even in areas contaminated by other gases. The gas sensor is located at the end of a 39 mm / 15.35 in flexible goose-neck tube, allowing unique access to hard-to-reach places.

Specification

General technical data	
Warm-up time	90 s
Operating time	40 h
Automatic power-off	10 min.
Refrigerant	R134a, R407C, R22, R410A, R404A
Other dimensions	Sensor length 390 mm
Sensitivity	selectable (high and low)
Protection class (device)	IP20
Battery/battery	4 x 1,5 V AA Battery (1,5V) , Alkali-Manganese
Battery capacity	3000 mAh
Operating conditions	-10 ... 60 °C , 0 ... 70 %RH
Storage conditions	-10 ... 60 °C , 0 ... 70 %RH
Dimensions (L x W x H)	173 x 66 x 56 mm
Weight	400 g

PCE Americas Inc. dba PCE Instruments
1201 Jupiter Park Drive, Suite 8
Jupiter, FL 33458
USA

Phone: +1-561-320-9162
info@pce-americas.com