MINI-DATALOGGER PCE-HT71-10-ICA

PCE-HT71N-10-ICA



- **Storage capacity: 32K**
- **USB port**
- **A software for calculating dew point and analysing data in a computer is**
- **included**
- **Wall mount included in the delivery**
- **Adjustable date/time clock (it loses 3 s / month)**
- **Adjustable measurement quota (2s ... 24h)**
- **Long-life lithium battery**
- **Non-volatile EEPROM**
- **Staus indicated by 2 LEDs (including alarm)**
- **Programmable alarm limits across entire measurement range**

The Data Logger detects air temperature and humidity and stores readings in its internal memory. The Data Logger has a compact format and a wide memory capacity (up to 32, values / 16, values for each parameter) and it is mainly used as a Data Logger in fields such as supermarket refrigeration units, refrigerated transport, warehouses, and other temperature controlled environments. The Data Logger works as a Data Logger to record climatological data in spaces with controlled ambient conditions. Data can be transferred to a computer or a laptop via the USB port. The Data Logger can be manually activated or can be programmed to start and stop on specific dates and times or to set the intervals at which measurements will be taken, allowing it to be left to record data in situ. Once transferred, data can be analysed on a computer. The software included in the delivery also calculates dew point. The internal clock allows the user to accurately assess the results.

Specification

Relative humidity	
Measuring range	0 ... 100 %RH
Resolution	0,1 %RH
Accuracy	±3% RH
Temperature	
Measuring range	-40 ... +70 °C
Resolution	0,1 °C
Accuracy	±1°C

General technical data	
Display Typ	without display
Storage medium	Internal memory
Storage capacity	32000 Values
Memory capacity Additional information	16000 per parameter
Storage interval from	2 s
Storage interval until	24 h
Interface	USB
Operating time	1 Year(s)
Housing	ABS
Protection class (device)	IP20
Battery/battery	10 x 3,6 V 1/2 AA 3.6 V LI-$SOCl_2$ (LS 14250) , lithium
Battery capacity	1200 mAh
Operating conditions	-40 ... 70 °C , 0 ... 100 %RH
Storage conditions	-40 ... 70 °C , 0 ... 100 %RH
Dimensions (L x W x H)	130 x 30 x 25 mm
Weight	20 g

PCE Americas Inc. dba PCE Instruments
1201 Jupiter Park Drive, Suite 8
Jupiter, FL 33458
USA

Phone: +1-561-320-9162
info@pce-americas.com