HANGING SCALE

PCE-HS 200N-ICA



- **Shackles and hooks included**
- **Accuracy ± 1% of full scale**
- **Robust metal housing**
- **Backlit LCD display**
- **Optionally with ISO calibration certificate**
- **incl. ISO-Calibration Certificate**

The hanging scales are available in the measuring ranges ... 2 kg / ... 44.9 lbs. With an accuracy of ± 1% of the measuring range, the hanging balance is a precise measuring device. The LCD display with a digit height of 22 mm in combination with the background lighting enables the readings of the hanging scales to be read even under difficult conditions. The sturdy metal housing of the hanging balance enables it to be used in harsh environments.

In addition to the unit kg, the measured values ⍰⍰of the hanging scales can also be displayed in lb and N. The hanging balance can freeze the currently displayed measured value using the "Hold" function. Adapters, product trays and other weighing accessories have their own weight, which is weighed and displayed by the hanging scale. For simplified weighing, the dead weight of the additionally attached devices can be tared off the hanging scales by pressing a button.

Specification

Weighing range	
Measuring range from	0 kg
Measuring range max.	200 kg
Resolution	50 g
Accuracy	±1 % v.Mb.

General technical data	
Units	kg, N, lb
Display Typ	LCD with illumination
Digit size [WxH]	Höhe: 22 mm
Automatic power-off	15 min.
Housing	Metal
Overload protection	Display in case of overload: "O_Ld"
Menu language	English (US), English (GB)
Protection class (device)	IP20
Power supply	batteries
Battery/battery	2 x 1,5 V AAA Battery (1,5V) , Alkali-Manganese
Battery capacity	1200 mAh
Operating conditions	5 ... 35 °C , 0 ... 90 %RH
Storage conditions	5 ... 35 °C , 0 ... 90 %RH
Dimensions (L x W x H)	158 x 84 x 37 mm
Weight	618 g

PCE Americas Inc. dba PCE Instruments
1201 Jupiter Park Drive, Suite 8
Jupiter, FL 33458
USA

Phone: +1-561-320-9162
info@pce-americas.com