CLAMP-ON ULTRASONIC FLOW METER

PCE-UFM 50PVC



- **measurement range 0.03 ... 5 m/s**
- **display of flow velocity, volume flow**
- **pipe size: DN50 (59 ... 67 mm)**
- **pipe material: PVC**
- **interface: Ethernet**
- **incl. reusable coupling pads**

Our clamp-on ultrasonic flow meter enables the measurement of flow velocity from 0.03 to 5 m/s. It can be used for measurements on PVC pipes with a diameter between 59 and 67 mm. The clamp-on ultrasonic flow meter of the PCE-UFM-PVC series uses the ultrasonic transit time method to determine velocity and flow volume. The flow meter has a separate external clamping device for easy installation without having to touch the liquid medium or stop the production. Special coupling pads ensure that this ultrasonic clamp-on system can also be used without contact gel.

The clamp-on ultrasonic flow meter is equipped with a 360° rotatable display that can be pointed in four directions (0°, 90°, 180°, 270°). The LCD colour display shows the flow velocity, date, time, signal quality, network connection status, instantaneous velocity and cumulative flow, among other parameters. The flow unit can be selected between m^3, l and gal.

The clamp-on ultrasonic flow meter uses Power over Ethernet (PoE) for power supply and Ethernet communication to save data to the cloud. This allows users to access, manage and analyse their measurement data at any time and from any location via mobile devices or computers without interrupting production processes. In water and wastewater management, drinking water treatment or in industry, flow meters are used in processes where water is used as a coolant, cleaning agent or component of production processes.

Specification

Speed	
Measuring range	0,03 ... 5 m/s
Resolution	0.01 m/s
Accuracy	±2 % of Rd (0.3 ... 5 m/s)
Speed	
Measuring range	0,1 ... 16 ft/s
Resolution	0.1 ft/s
Accuracy	±2 % of Rd (1.0 ... 16 ft/s)
Volume flow	
Measuring range	0,2 ... 35 m^3/h
Resolution	0,01 m^3/h
Accuracy	±2 % of Rd

General technical data	
Display type	LC colour display
Display size	1,44 Inch
Display resolution	128 x 128
Interface	Ethernet, PoE
Materials	PVC
Measured medium	Water
Repeatability	0,2 %
Communication	HTTP, MQTT
Menu language	English, Chinese, English (GB)
Protection class (device)	IP54
Power supply	PoE
Connector type	RJ45
Operating conditions	-10 ... 50 °C , 0 ... 99 % RH
Storage conditions	-10 ... 50 °C , 0 ... 99 % RH
Dimensions (L x W x D)	65 x 111 x 43 mm
Weight	1252 g