INDUSTRIAL SILO SCALE

PCE-SDF 60





- **1 switching outputs for OK status**
- **1 switching output for critical level**
- **1 switching output for withdrawal deviation**
- **1 switching contact for function interruption**
- **Bidirectional RS-232 interface**
- **Suitable for continuous measurement**

The industrial silo scale for containers - fill level - removal - monitoring - offers the possibility to ensure the supply of a production facility effectively and reliably. The silo scale for container monitoring can not only monitor the current filling level of the container but also the continuous weight loss. By monitoring the current filling level, the silo scale for container - filling level - removal - monitoring - can prompt the machine operator to fill up the container in good time. For this purpose, the silo scale for container monitoring has three passive switching contacts (potential-free contact / optocoupler outputs / OC). A switching contact of the monitoring silo scale can be used for a green traffic light, for example. This switching contact is active when the actual status of the container is OK.

If the container reaches a minimum limit / minimum load, a second switching contact can switch a yellow or red traffic light, which is intended to prompt the user to fill up. The traffic lights are not included in the scope of delivery, but can be ordered as an option for the silo scale for container monitoring. The second monitoring option of the silo scale is the continuous weight loss. This function can monitor the filling processes of the machines and report irregularities in material removal. A weight loss per unit of time can be stored in the silo scale for containers - level - removal - monitoring. Example g/min, kg/min, g/hour, kg/hour.

Specification

Weighing range	
Measuring range from	400 g
Measurement range up to [Max]	60 kg
Resolution [d]	2 g
Accuracy	±8 g

General technical data	
Cable length	1,5 m
Measuring functions	MIN, MAX, Average value
Measuring functions (additional information)	Piece counting function, totalising function, percentage weighing, recipe weighing, statistics function, animal weighing function
Units	kg, g, lb, oz, ct, ozt, gr, dwt
Display type	LED
Digit size [WxH]	Height: 18 mm
Interface	bidirectional RS232
Automatic power-off	5 min
Repeatability	4 g
Minimum load [min]	400 g
Tare range	Multiple tare over the full measurement range
Calibration	external
Dimensions	Display 190 x 140 x 65 mm
Settling time	< 3 s
Linearity	6 g
Menu language	English, English (GB)
Protection class (device)	IP54, IP65
Power supply	230V AC | 50 Hz, 8 VA 12V DC, 850 mA
Connector type	Device-europlug
Operating conditions	-10 ... 40 °C , 20 ... 90 (non-condensing)% RH
Storage conditions	-10 ... 40 °C , 0 ... 90 % RH
Dimensions (L x W x H)	400 x 500 x 125 mm
Weight	12000 g

PCE Instruments UK Ltd.
Chester Rd, Old Trafford Suite 1N-B, Trafford House, M32 0RS Manchester
Great Britain

Phone: +44 (0) 161 4649020
info@pce-instruments.co.uk